

CORRIGENDUM NOTICE - No- 2

e-Tender for Procurement of Printer for GRIDCO and OPTCL **(e-Tender No. TW-IT/OT/06/2017-18)**

The following revision/update has been made in the tender specification:

1. MFP PRINTER SPECIFICATION (Quantity: 55 Nos.)

Sl. No.	Specification	Detail Description
1.	Print Speed	Normal, A4: min 25 ppm
2.	First Page Out	As fast as 8 sec or less
3.	Print Resolution	Min 1200 x 1200 dpi
4.	Processor	600 MHz
5.	Memory	256 MB or More
6.	Duty Cycle (monthly, A4)	15,000 pages or More
7.	Input Tray	Min 250-sheet input tray, Min 35 sheet Automatic Document Feeder
8.	Output Tray	150 or More-sheet output tray
9.	Duplex Printing	Automatic
10.	Standard connectivity	Hi-Speed USB 2.0 port (host/device); built-in Fast Ethernet 10/100Base-TX network port; Phone line port (in/out)
11.	Scan Speed	14 ppm or Higher (b & w), up to 5 ppm or higher(colour)
12.	Scan resolution	Min 300 x 300 dpi (colour and mono, ADF);
13.	Scan file format	JPEG, PDF, PNG
14.	Flatbed Scanning	Required
15.	Copy Speed	Min 25 cpm black
16.	Copy resolution	600 x 600 dpi
17.	Copier resize	25 to 400%
18.	Fax Speed	Max 3 sec per page
19.	Fax speed dialing (max numbers)	Up to 120 numbers
20.	Power	Power Input: 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), Power consumption: maximum 500 watts
21.	Operating System	Microsoft Windows® 7 & Win 8,10, Linux, Mac OS
22.	Fax features	Auto fax reduction supported: Yes; Auto-Redialing: Yes; Fax delayed sending: Yes; Distinctive ring detection supported: Yes; Fax forwarding supported: Yes;

2. A4-SIZE COLOUR LASER PRINTER (Quantity: 5 Nos.)

Sl. No.	Specification	Detail Description
1.	Print Technology	Laser
2.	Print Speed	Normal, A4: Up to 25 ppm B/W & Color
3.	First Page Out	As fast as 8 sec
4.	Print Resolution	Up to 1200 x 1200 dpi
5.	Processor Speed	1200 MHz or above
6.	Memory	256 MB or Higher
7.	Duty Cycle (monthly, A4)	Min 4,000 pages
8.	Input Tray	250-sheet input tray, 35 sheet Automatic Document Feeder
9.	Output Tray	Min 150-sheet output tray
10.	Duplex Printing	Automatic
11.	Connectivity	<ul style="list-style-type: none">• Hi-Speed USB 2.0 port• built-in Gigabit Ethernet 10/100/1000 Base-TX network port
12.	Power	Power Input :220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) Power consumption: Maximum 600 watts
13.	Operating System	Microsoft Windows® 7 & Win 8,10, Linux, Mac OS

Chief General Manager (IT)
OPTCL