

ଓଡ଼ିଶା ବିଦ୍ୟୁତ ଶକ୍ତି ସଂଚାରଣ ନିଗମ ଲିଃ.

ODISHA POWER TRANSMISSION CORPORATION LTD.
O/O: G.M. (ELECT.) E.H.T. (O&M) CIRCLE, BURLA,

DIST: SAMBALPUR (ODISHA) 768017

CORRIGENDUM TO E-TENDER CALL NOTICE NO. BRL-15/2024-25

NO.- EHTM/BRL/e-TENDER/ 1247

DATE: 22.10.2024

CORRIGENDUM

With reference to the E-Tender call notice No. BRL-15/2024-25, the last date of sale, receipt and opening of tender paper is hereby extended as given below. Also the tender specification has been updated as follows.

Date of Sale of Tender Paper	:	Up to 29.10.2024 at
-		www.tenderwizard.com/OPTCL
Last Date & time of receipt of Tender	:	30.10.2024 up to 01:00 PM at EHT (O&M)
Documents		Circle, Burla.
Date of Opening of Tender Paper	:	On 30.10.2024 at 4:00 PM
(Technical Bid only)		
Date of Opening of financial bid		Will be intimated later those who have
(Those who have qualified in technical bid only)		qualified in technical bid.

TECHNICAL SPECIFICATION

		400KV Discharge Rod
1.	Material	FRP PPULTRUDED
2.	Surface	SMOOTH AND GLOSSY
3.	Total section	3 section
4.	Stick Design	CIRCULAR DESIGN
5.	Locking	PUSH BUTTON TYPE LOCKING TYPE
6.	Assembled Length	18 FEET
7.	Insulator	TOP & BOTTOM SECTION PROVIDED WITH SAFE
		GUARD
8.	H.V Test	630KV (Type test) from ERDA or any accredited
		laboratories
9.	Standard	IEC 60060
10	Glass content	60%
11	Top section dia	38MM
12	Bottom section dia	38MM
13	Grip	RUBBER GRIP
14	Earthing cable (PVC insulated)	ISI mark PVC insulated multi stranded 440/1100V - grade
		transparent copper cable.
		Copper-35mm ² , 15 meters.

220KV Discharge Rod			
1.	Material	FRP PPULTRUDED	
2.	Surface	SMOOTH AND GLOSSY	
3.	Total section	3 Section	
4.	Design	PUSH BUTTON TYPE	
5.	Locking	PUSH BUTTON TYPE LOCKING TYPE	
6.	Assembled Length	18 FEET	
7.	Insulator	TOP & BOTTOM SECTION PROVIDED WITH	
	,	SAFE GUARD	
8.	H.V Test	510KV (Type test) from ERDA or any accredited	
		laboratories	
9.	Standard	IEC 60060	
10.	Glass content	60%	
1 f.	Top section dia	38MM	
12.	Bottom section dia	38MM	
13.	Grip	RUBBER GRIP	
14.	Earthing cable (PVC	ISI mark PVC insulated multi stranded 440/1100V -	
	insulated)	grade transparent copper cable.	
		Copper-35mm ² , 15 meters	

All other terms & conditions will remain constant.

N.B:- All subsequent addendums/corrigendum to the tender shall be hosted in the OPTCL's official web site http://www.optcl.co.in.

General Manager (Elect.) E.H.T. (O&M) Circle, Burla